CLAIMS

Please rewrite the claims as set forth below. The listing of claims replaces all prior versions and listings of claims in the application:

1. (PREVIOUSLY PRESENTED) A method for generating a reference transmission signal for use in testing a communications system, comprising:

capturing a data packet transmission signal containing a plurality of reference data; digitizing said data packet transmission signal;

retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data;

modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal;

storing said digital transmission signal following said modulating of said carrier signal and prior to a use of said digital transmission signal in producing said reference transmission signal for transmission and demodulation;

retrieving said stored digital transmission signal; and

frequency up-converting said retrieved digital transmission signal to produce said reference transmission signal.

- 2. (ORIGINAL) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as an analog signal.
- 3. (ORIGINAL) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as a wireless signal.
- 4. (ORIGINAL) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as a wired signal.

10/769,971 Patent

AMENDMENT E

5. (ORIGINAL) The method of claim 1, wherein said retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data comprises demodulating at least a selected portion of said digitized data packet transmission signal to produce a plurality of demodulated data.

- 6. (ORIGINAL) The method of claim 1, wherein said retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data comprises decoding at least a selected portion of said digitized data packet transmission signal to produce a plurality of decoded data.
- 7. (ORIGINAL) The method of claim 1, wherein said modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal comprises encoding said carrier signal with said plurality of retrieved data.
- 8. (ORIGINAL) The method of claim 1, wherein said storing said digital transmission signal comprises storing said digital transmission signal in memory.
- 9. (PREVIOUSLY PRESENTED) The method of claim 1, further comprising modifying one or more selected bits of said plurality of retrieved data prior to said modulating a carrier signal with said plurality of retrieved data to produce said digital transmission signal.
 - 10. *(CANCELED)*
 - 11. *(CANCELED)*
- 12. *(CURRENTLY AMENDED)* An apparatus including circuitry for generating a reference transmission signal for use in testing a communications system, comprising:

signal capture means for capturing a data packet transmission signal containing a plurality of reference data;

digitizer means for digitizing said data packet transmission signal;

first data retrieval means for retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data;

signal modulator means for modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal;

storage means for storing said digital transmission signal following said modulating of said carrier signal and prior to a use of said digital transmission signal in producing said reference transmission signal for transmission and[[;]] demodulation;

second data retrieval means for retrieving said stored digital transmission signal; and frequency conversion means for frequency up-converting said retrieved digital transmission signal to produce said reference transmission signal.

- 13. (ORIGINAL) The apparatus of claim 12, further comprising data modifier means for modifying one or more selected bits of said plurality of retrieved data prior to said modulation of a carrier signal with said plurality of retrieved data to produce a digital transmission signal.
 - 14. *(CANCELED)*
 - 15. *(CANCELED)*